## Florida International University FIU Digital Commons

### SERC Research Reports

Southeast Environmental Research Center

2011

# 2011 Annual Report of the Water Quality Monitoring Project for the Southeast Florida Coral Reef Initiative (SEFCRI)

Joseph N. Boyer Southeast Environmental Research Center, Florida International University, boyerj@fiu.edu

Henry O. Briceño Southeast Environmental Research Center, Florida International University, bricenoh@fiu.edu

Jeff Absten Southeast Environmental Research Center, Florida International University

David Gilliam Nova Southeastern University Oceanographic Center, National Coral Reef Institute

Dick Dodge Nova Southeastern University Oceanographic Center, National Coral Reef Institute

Follow this and additional works at: https://digitalcommons.fiu.edu/sercrp

Part of the Environmental Health and Protection Commons, Environmental Monitoring Commons, Natural Resources and Conservation Commons, and the Water Resource Management Commons

### **Recommended** Citation

Boyer, Joseph N.; Briceño, Henry O.; Absten, Jeff; Gilliam, David; and Dodge, Dick, "2011 Annual Report of the Water Quality Monitoring Project for the Southeast Florida Coral Reef Initiative (SEFCRI)" (2011). SERC Research Reports. 72. https://digitalcommons.fu.edu/sercrp/72

This work is brought to you for free and open access by the Southeast Environmental Research Center at FIU Digital Commons. It has been accepted for inclusion in SERC Research Reports by an authorized administrator of FIU Digital Commons. For more information, please contact dcc@fiu.edu.

## 2011 ANNUAL REPORT OF THE WATER QUALITY MONITORING PROJECT FOR THE SOUTHEAST FLORIDA CORAL REEF INITIATIVE (SEFCRI)



Joseph N. Boyer, Henry O. Briceño, and Jeff Absten Southeast Environmental Research Center OE-148, Florida International University Miami, FL 33199 <u>http://serc.fiu.edu/wqmnetwork/</u>

David Gilliam and Dick Dodge Nova Southeastern University Oceanographic Center National Coral Reef Institute 8000 North Ocean Drive, Dania Beach, FL 33004 <u>http://www.nova.edu/ocean/</u>

### 2011 ANNUAL REPORT OF THE WATER QUALITY MONITORING PROJECT FOR THE SOUTHEAST FLORIDA CORAL REEF INITIATIVE (SEFCRI)

Joseph N. Boyer, Henry O. Briceño, and Jeff Absten Southeast Environmental Research Center OE-148, Florida International University Miami, FL 33199

David Gilliam and Dick Dodge Nova Southeastern University Oceanographic Center National Coral Reef Institute 8000 North Ocean Drive, Dania Beach, FL 33004

Funded by NOAA Award #NA09NOS4260253, NOAA Award #NAI0NOS4260221, US EPA Agreement #X7-96410604-5, and US EPA Agreement #X7-95469410-0

#### **EXECUTIVE SUMMARY**

This report serves as a summary of our efforts to date in the execution of the Water Quality Monitoring Project for the Southeast Florida Coral Reef Initiative (SEFCRI). The period of record for this report is Dec. 2009 – Sep. 2011 and includes data from 8 quarterly sampling events at 22 stations along the coast including Miami-Dade, Broward, Palm Beach, and Martin Counties.

Field parameters measured at each station include salinity (practical salinity scale), temperature ( $^{\circ}C$ ), dissolved oxygen (DO, mg  $^{-1}$ ), turbidity (NTU), and light attenuation (K<sub>d</sub>, m<sup>-1</sup>). Water quality variables include the dissolved nutrients nitrate (NO<sub>3</sub><sup>-</sup>), nitrite (NO<sub>2</sub><sup>-</sup>), ammonium (NH<sub>4</sub><sup>+</sup>), dissolved inorganic nitrogen (DIN), and soluble reactive phosphate (SRP). Total unfiltered concentrations include those of nitrogen (TN), organic nitrogen (TON), organic carbon (TOC), phosphorus (TP), silicate (SiO<sub>2</sub>) and chlorophyll *a* (CHLA,  $\mu$ g l<sup>-1</sup>). All values are reported in ppm unless noted otherwise.

Although this project is relatively new, several important results have been realized so far. First, is documentation of differences in water quality among regions as clustered by county. Ongoing quarterly sampling of 22 stations in the SEFCRI has provided us with the ability to explore the spatial component of water quality variability in the region. By stratifying the sampling stations according to county we report some interpretations as to the relative importance of external vs. internal factors on the ambient water quality within the SEFCRI. The general consensus, for only 8 sampling event, is that the overall water quality is very good but that there are large excursions from the median due to events. Sites off Martin County were slightly elevated in DIN, TP, and CHLA but lower in salinity. We ascribe these localized effects to terrestrial freshwater inputs from the Loxahatchee River.

Trend analysis was not performed as there were only 8 sampling events spread over 2 years. However, seasonal differences were pronounced in some variables due to differences in water patterns and precipitation/terrestrial inputs between wet and dry periods.

The large scale of this monitoring program has allowed us to assemble a much more holistic view of broad physical/chemical/biological interactions occurring over the South Florida hydroscape.

2

Much information has been gained by inference from this type of data collection program in a sister program, the Florida Keys National Marine Sanctuary: major nutrient sources have be confirmed, relative differences in geographical determinants of water quality have been demonstrated, and large scale transport via circulation pathways have been elucidated. In addition we have shown the importance of looking "outside the box" for questions asked within. Rather than thinking of water quality monitoring as being a static, non-scientific pursuit it should be viewed as a tool for answering management questions and developing new scientific hypotheses. We expect that continued monitoring of SEFCRI will answer some of these same questions.

We continue to maintain a website (<u>http://serc.fiu.edu/wqmnetwork/</u>) where data and reports from the SEFCRI Project are available.

## **2011 ANNUAL REPORT** OF THE WATER QUALITY MONITORING PROJECT FOR THE SOUTHEAST FLORIDA CORAL REEF INITIATIVE (SEFCRI)

Principal Investigators: Joseph N. Boyer, Henry O. Briceño, and Jeff Absten Southeast Environmental Research Center OE-148, Florida International University Miami, FL 33199 <u>http://serc.fiu.edu/wqmnetwork/</u>

David Gilliam and Dick Dodge Nova Southeastern University Oceanographic Center National Coral Reef Institute 8000 North Ocean Drive, Dania Beach, FL 33004 <u>http://www.nova.edu/ocean/</u>

> Funded by: NOAA Award #NA09NOS4260253 NOAA Award #NAI0NOS4260221 US EPA Agreement #X7-96410604-5 US EPA Agreement #X7-95469410-0

This is Technical Report #542 of the Southeast Environmental Research Center at Florida International University and Publication #141 of the National Coral Reef Institute at Nova Southeastern University.

### 1. Background

The counties of Southeast Florida (Miami Dade, Broward, Palm Beach, and Martin) are highly urbanized, containing one third of Florida's population of 18 million people with development occurring directly along the coast. Due to the close proximity of the northern Florida Reef Tract to the urbanized shoreline, ~1.5 km from shore, southeast Florida's coral reefs are directly impacted by anthropogenic stressors. Terrestrial runoff and wastewater effluent disposal methods may be impacting the reef resource by degrading the water quality. However, to date, minimal offshore water quality monitoring, needed to determine these impacts, has been conducted in the southeast Florida region. The objective of the Southeast Florida Coral Reef Water Quality Monitoring Project (SECREMP) is to determine if there is a decline or recovery of coastal and offshore water quality in Southeast Florida and if water quality may be linked to land-based sources of pollution, or changes in coral condition.

Due to the extent (~105 miles) of the southeast Florida coast geographic gaps ranging from 30-50 km exist between these sampling sites. These gaps and the lack of understanding of inshore to offshore fate of nutrients fate limit the ability to develop land-based nutrient loads for the reef tract. We expect that this rudimentary water quality monitoring program will begin to address this issue.

### 2. Project History

A NOAA CRCP grant in FY09 to the National Coral Reef Institute at Nova Southeastern University (NSU-NCRI) allowed for one year of baseline water quality data to be collected at the 17 SECREMP monitoring sites. The first water sample collection occurred December 2009. A subsequent proposal was awarded for FY10 under the same program to provide for water quality sampling and analysis through September 2011. A grant from EPA Region 4 to the Southeast Environmental Research Center at Florida International University (FIU-SERC) provided funds to continue monitoring and to add 5 sites (22 total) to fill in some geographic gaps in monitoring and assist in developing onshore to offshore water quality trends. Sites were located in the geographic gaps at other SECREMP sites in an effort to relate water quality with changes in the reef health (e.g. coral cover declines).

In a collaborative effort between NOAA, EPA, the Florida Department of Environmental Protection's Coral Reef Conservation Program (FDEP-CRCP), NSU-NCRI, and FIU-SERC, a coastal water quality monitoring program for southeast Florida will be implemented using similar water sampling methods and standards used for the Florida Keys National Marine Sanctuary (FKNMS) Water Quality Protection Program (<u>http://floridakeys.noaa.gov/wqpp/welcome.html</u>). The SEFCRI Water Quality Monitoring Project consists of quarterly surveys during which physical, chemical, and biological water quality parameters were measured and water samples collected for laboratory analysis. Long-term funding is currently being sought to maintain and expand the water quality monitoring program.

### 3. Benefit

The general objective of water quality monitoring is to measure the status and trends of water quality parameters to evaluate progress toward achieving and maintaining water quality standards and protecting and restoring the living marine resources of the ecosystem. SEFCRI Water Quality Monitoring Project data will be used to assist in resource protection and management decisions for the southeast Florida region. Specific objectives of this project are as follows:

- To provide data needed to make unbiased statements about the status of water quality parameters in the southeast Florida region as a whole, and within defined strata; and with continued funding support for a long term water quality monitoring program, statistically rigorous statements about the status and temporal trends of water quality can be incorporated
- To help define reference conditions in order to develop resource-based water quality standards (biocriteria)
- To provide a framework for testing hypothesized pollutant fate/effect relationships through process-oriented research and monitoring
- To assist with making informed management actions and policy development processes for improved coral reef resource conservation in Florida

## 4. Methods

Field sampling was performed quarterly at 17 SECREMP sites (2010, thereafter at 22 sites) by staff from the NSU-NCRI (Fig. 1). Sampling was conducted from small boats with facilities for sample processing on board and equipped to satisfy the technical and safety requirements of the project. Semi-continuous measurements were made throughout the water column using the Seabird CTD to generate a depth profile of each of the following variables: depth (m), temperature (°C), salinity (PSU), dissolved oxygen (DO, mg l<sup>-1</sup>), and photosynthetically active radiation (PAR,  $\mu$ E m<sup>-2</sup> s<sup>-1</sup>). The vertical light attenuation coefficient (K<sub>d</sub> in m<sup>-1</sup>) was calculated for the cast as a log function from PAR measurements through the water column.



Figure 1. Map of SEFCRI region showing field sampling sites distributed along coast.

Water samples were collected at depth and at the surface at each site using a Niskin bottle sampler, preserved on ice and transported to FIU-SERC for nutrient analysis. Samples were analyzed for ammonium (NH<sub>4</sub><sup>+</sup>), nitrate+nitrite (NO<sub>x</sub><sup>-</sup>), nitrite (NO<sub>2</sub><sup>-</sup>), total nitrogen (TN), soluble reactive phosphorus (SRP), total phosphorus (TP), total organic carbon (TOC), silicate (SiO<sub>2</sub>), chlorophyll *a* (CHLA,  $\mu$ g l<sup>-1</sup>), and turbidity (NTU) using standard laboratory methods. Some parameters were not measured directly but calculated by difference. Nitrate (NO<sub>3</sub><sup>-</sup>) was calculated as NO<sub>X</sub><sup>-</sup> - NO<sub>2</sub><sup>-</sup>; total dissolved inorganic nitrogen (DIN) as NO<sub>X</sub><sup>-</sup> + NH<sub>4</sub><sup>+</sup>., and total organic nitrogen (TON) as TN - DIN. All variables are reported in ppm (mg l<sup>-1</sup>) unless otherwise noted.

Dissolved nutrients were defined using Whatman GF/F filters with a nominal pore size of 0.8  $\mu$ m. A 60 ml sample was collected from a Niskin bottle using a syringe and filtered through a 25 mm Whatman GF/F filter. The filtrate was collected in a 60 ml high density polyethylene (HDPE) bottle and the filter stored in a vial with 90% acetone for extraction of CHLA. An

additional 120 ml sample was collected directly from the Niskin bottle for analysis of TN, TP, and turbidity.

 $NH_4^+$  was analyzed by the indophenol method (Koroleff 1983).  $NO_2^-$  was analyzed using the diazo method and  $NO_x^-$  was measured as nitrite after cadmium reduction (Grassoff 1983a,b). The ascorbic acid/molybdate method was used to determine SRP (Murphy and Riley 1962). High temperature combustion and high temperature digestion were used to measure TN (Frankovich and Jones 1998; Walsh 1989) and TP (Solórzano and Sharp 1980), respectively. TOC was determined using the high temperature combustion method of Sugimura and Suzuki (1988). Silicate was measured using the heteropoly blue method (APHA 1995). Detailed protocols are presented in EPA (1993).

Samples were analyzed for CHLA content by spectrofluorometry of acetone extracts (Yentsch and Menzel 1963). Protocols are presented in EPA (1993) and elsewhere as noted.

In accordance with EPA policy, the SEFCRI water quality monitoring program will adhere to existing rules and regulations governing QA and QC procedures as described in EPA guidance documents. The principal investigator will consult with the EPA Region IV QA/QC Officer on any issues involving QA/QC matters.

### 5. Results

We have found that water quality monitoring programs composed of many sampling stations situated across a diverse hydroscape are often difficult to interpret due to the "can't see the forest for the trees" problem (Boyer et al. 2000). At each site, the many measured variables are independently analyzed, individually graphed, and separately summarized in tables. This approach makes it difficult to see the larger, regional picture or to determine any associations among sites. In order to gain a better understanding of the spatial patterns of water quality of the SEFCRI, we attempted to reduce the data matrix into fewer elements which would provide robust estimates of condition and connection. Ongoing quarterly sampling of 22 stations in the SEFCRI has provided us with the ability to explore the spatial component of water quality variability in the region. By stratifying the sampling stations according to county we report some interpretations as to the relative importance of external vs. internal factors on the ambient water quality within the SEFCRI (Fig. 2). The general consensus, for only 8 sampling event, is that the overall water quality is very good but that there are large excursions from median due to events.



*Figure 1. Box-and-whisker plots showing median and distribution of variables from 8 sampling events as grouped by County.* 

Dissolved inorganic N in all regions is generally at or below 10 **ppb**, a very low value and indicative of oceanic conditions. Ammonium is typically higher than nitrate as would be expected. CHLA is generally less than 0.5 ppb except for sites off Martin County where values a slightly higher. Total N in all areas is below 0.1 ppm and Total P is around 5 **ppb**, except for sites off Martin County which are significantly higher, but still under 10 **ppb** (Fig. 2).

DO ranges between 6 and 7 ppm for all areas with no excursions less than 4 ppm. Turbidity is also low (typically under 0.5 NTU) and this is reflected in the low light extinction coefficients ( $K_d$ ). Salinity ranges between 35 and 36.5 but the sites off Martin County experience lowest salinity events down to 33. We expect this is due to freshwater releases from the Loxahatchee River.

Along with spatial differences in water quality, there are differences with depth as well. Table 1 shows those areas having significant differences between surface and bottom waters. Dissolved inorganic N is typically higher in surface waters while salinity is lower. This is evidence of freshwater loading to surface from terrestrial and atmospheric sources. Slightly higher CHLA in surface and higher Total P in bottom is indicative of P uptake by phytoplankton in surface waters. Oddly, we found DO to be higher in bottom waters but this may be due to generally lower temperatures in this region.

	County Region			
		Miami-	Palm	
	Broward	Dade	Beach	Martin
NOx	0.003	0.004	0.001	0.02
$NH_4^+$	0.09	NS	0.09	NS
TN	0.09	NS	NS	0.07
ТР	0.005	NS	0.003	0.08
тос	0.04	NS	NS	0.05
SiO <sub>2</sub>	NS	NS	NS	NS
CHLA	0.01	NS	0.07	0.02
Turbidity	NS	NS	NS	NS
Salinity	0.001	0.001	0.001	0.001
Temp.	0.08	0.02	0.001	0.007
DO	0.02	0.04	0.07	NS
surface is greater				
bottom is greater				

**Table 1.** Difference between surface and bottom concentrations of variables by county grouping from Kruskall-Wallace test of significance (p<0.10). Values in **green** denote surface values being higher than bottom. Values in **red** mean bottom values are greater than those at the surface.

Trend analysis was not performed as there are only 8 sampling events spread over 2 years. However, seasonal differences were pronounced in some variables due to differences in water patterns and precipitation/terrestrial inputs between wet and dry periods. Examples are shown in Fig. 2-6.

This brings up another important point; when looking at what are perceived to be local trends, we find that they seem to occur across the whole region but at more damped amplitudes. This spatial autocorrelation in water quality is an inherent property of highly interconnected systems such as coastal and estuarine ecosystems driven by similar hydrological and climatological forcing. It is clear that trends observed inside the SEFCRI are influenced by external, regional conditions.

The large scale of this monitoring program has allowed us to assemble a much more holistic view of broad physical/chemical/biological interactions occurring over the South Florida hydroscape. Much information has been gained by inference from this type of data collection program in a sister program, the Florida Keys National Marine Sanctuary: major nutrient sources have be confirmed, relative differences in geographical determinants of water quality have been demonstrated, and large scale transport via circulation pathways have been elucidated. In addition we have shown the importance of looking "outside the box" for questions asked within. Rather than thinking of water quality monitoring as being a static, non-scientific pursuit it should be viewed as a tool for answering management questions and developing new scientific hypotheses. We expect that continued monitoring of SEFCRI will answer some of these same questions.

We continue to maintain a website (<u>http://serc.fiu.edu/wqmnetwork/</u>) where data and reports from the SEFCRI Project are available.











### 6. References

- APHA. 1995. Automated method for molybdate-reactive silica. In A. D. Eaton, L. S. Clesceri, and A. E. Greenberg (Eds.), Standard Methods for the Examination of Water and Wastewater.
- Boyer, J. N., P. Sterling, and R. D. Jones. 2000. Maximizing Information from a Water Quality Monitoring Network through Visualization Techniques. Estuarine, Coastal and Shelf Science 50: 39-48.
- EPA. 1979. Handbook for Analytical Quality Control in Water and Wastewater Laboratories. EPA 600/4-79-019. Environmental Protection Agency, Environmental Monitoring and Support Laboratory, Cincinnati, OH.
- EPA. 1993. Water Quality Protection Program for the Florida Keys national Marine Sanctuary: Phase II Report. Battelle Ocean Sciences, Duxbury, MA and Continental Shelf Associates, Inc., Jupiter, FL.
- Grasshoff, K. 1983a. Determination of nitrate. In K. Grasshoff, M. Erhardt, and K. Kremeling (Eds.), Methods of Seawater Analysis. Verlag Chemie, Weinheim, Germany.
- Grasshoff, K. 1983b. Determination of nitrite. In K. Grasshoff, M. Erhardt, and K. Kremeling (Eds.), Methods of Seawater Analysis. Verlag Chemie, Weinheim, Germany.
- Frankovich, T. A., and R. D. Jones. 1998. A rapid, precise, and sensitive method for the determination of total nitrogen in natural waters. Mar. Chem. 60:227-234.
- Koroleff, F. 1983. Determination of ammonia. In K. Grasshoff, M. Erhardt, and K. Kremeling (Eds.), Methods of Seawater Analysis. Verlag Chemie, Weinheim, Germany.
- Murphy, J., and J. P. Riley. 1962. A modified single solution method for the determination of phosphate in natural water. Anal. Chim. Acta 27: 31-36.
- Solórzano, L. and J. Sharp. 1980. Determination of total dissolved phosphorus and particulate phosphorus in natural waters. Limnol. Oceanogr. 25: 754-758.
- Walsh, T. W. 1989. Total dissolved nitrogen in seawater: a new high temperature combustion method and a comparison with photo-oxidation. Mar. Chem. 26: 295-311.
- Yentsch, C. S., and D. W. Menzel. 1963. A method for determination of phytoplankton chlorophyll and phaeophytin by fluorescence. Deep Sea Res. 10: 221-231.